## **LARK SPK6**

# **Active Speaker**



### **Product Introduction**

The LARK SPK6 system is a professional sound reinforcement speaker specially tuned for classroom, the main speaker promotes the sub-speaker, no need to add additional amplifier equipment. Amplifier module with independent volume adjustment, 3pin Phoenix terminal mono balanced input, RCA stereo input; built-in DSP optimization to ensure voice clarity; amplifier module contains overload protection, short circuit protection and other functions.

#### **Product Features**

- Integrated Class D digital amplifier, high efficiency and energy saving;
- ♦ Overload, short circuit, overheating protection circuit;
- ♦ Wall mounting design;
- ♦ Providing 3pin Phoenix terminal mono differential input;
- ♦ Provide DC 12V output;
- ♦ The main box pushes the sub box without additional amplifier equipment.



## **Specification**

Frequency Response (-10dB)	100∼20kHz
Tweeter	1×20mm voice coil tweeter
Woofer	1×6", 25mm voice coil
Power Rating	60W
Sensitivity (1W/1M)	90dB
Maximum Sound Pressure Level	108dB (114dB Peak)
Impedance	4Ω
Audio Interface	Phoenix terminal balanced input; RCA stereo input; Speaker output terminals (output to sub speaker)
Salve Speaker audio interface	Speaker terminal block
Power Supply	AC 220V/50Hz
Speaker Dimensions (H×W×D)	300×220×150mm
Package Dimensions (H×W×D)	430×280×365mm
Weight	8.5kg/Pair

