

SWIFT X Series

Digital Signal Processor



8 In 8 Out SWIFT X88N



16 In 16 Out SWIFT X1616N

Product Introduction

The Digital Signal Processor equipped with a high-performance 32-bit floating-point DSP processor and 24-bit A/D ~ D/A converter, 48kHz sampling rate, DSP processing bus structure built-in Acoustic Feedback Canceler, Acoustic Echo Canceler, Adaptive Noise Suppressor, Automatic Mixer and other audio core algorithms, to restore high-quality sound, with a comprehensive matrix mixing function. It supports multiple scene presets, scene saving and other functions, and user-friendly control software interface. Mainly used in a variety of large places, can meet the theatre, concert halls, remote video conferencing, stadiums, churches, conference center, theme parks, public sound reinforcement systems and other aspects of the application needs.

Functions

- ✧ Comprehensive matrix mixing function, 48kHz sampling rate, 24-bit high performance A/D, D/A converter and 32-bit floating point DSP processor;

- ✧ DSP audio processing, built-in automatic mixing console, including mixing and automatic mixing functions, but also has a mixing component control function; at the same time with AFC, AEC, ANS component; AFC: Support notch feedback cancellation algorithm, manual and automatic notch feedback canceler, with manual, dynamic, fixed three modes, can automatically capture the feedback point or manually set the feedback point, the maximum support for the capture of 16 feedback points, the maximum depth of inhibition up to 24dB;
- ✧ Inputs per channel: Preamplifier 42dB, Invert, Signal Generator, Expander, 5-band Parametric Equalizer, Compressor, Automatic Gain Control (AGC), AM (Gain Sharing Automatic Mixer or Gating Automatic Mixer), Acoustic Feedback Canceler (AFC), Acoustic Echo Canceler (AEC), Adaptive Noise Suppressor (ANS), Parametric Equalizer filter type selectable (Low Shelf, High Shelf, Low Pass Filter, High Pass Filter);
- ✧ Outputs per channel: Delay, Crossover, 31-band Graphic Equalizer, Limiter, Invert,;
- ✧ Test signal generator, Sine wave, Pink Noise, White Noise, frequency and level magnitude selectable;
- ✧ Input phase button, mute button, phantom power button;
- ✧ Output mute button, phase button per channel;
- ✧ One-click display of all function modules;
- ✧ Storing user manual and software with the device;
- ✧ Central control code generated in the control software; power failure automatic protection memory function; one-click reset function;
- ✧ Channel copy, paste, group control function;
- ✧ Supports setting the maximum and minimum volume range for each channel;
- ✧ The same host allows 10 users to manage;
- ✧ Device name can be modified;
- ✧ Editable preset mode, new, delete, modify, one-click reset, preset mode can be stored to computer and one-click reset;
- ✧ With camera tracking function, can independently adjust the preset position of a camera, compatible with VISCA, PELCO-D, PELCO-P three control protocols, support for custom commands;
- ✧ Ethernet multi-purpose data transmission and control port, can support real-time management of single and multiple devices;

- ✧ Intuitive image, simple and easy to understand the graphical software control interface, for customers to bring fast, real-time operating experience;
- ✧ The device does not need a CD, comes with installation software, a device for a software version, to solve the troubles caused by the loss of the installation CD and the confusion of multiple software versions;
- ✧ Configuration of bi-directional RS485 interface, standard Ethernet control interface, 2-channel programmable GPIO control interface (customisable inputs and outputs);
- ✧ Support 100 groups of scene presets, scene new, save, delete and other functions;
- ✧ Intuitive, graphical software control interface, works on Windows XP, 7, 8, 10, 11, etc.;
- ✧ Support mobile iOS, iPadOS, Android control software.

Specification

Category	Parameter Item	Parameter Description
Peripherals	Input Interfaces	8/16 Analog
	Output Interfaces	8/16 Analog
	Control Interfaces	1 RJ45 interface, 1 RS485 interface, 2 GPIO control interface
Audio processing	Processor	TI 456MHz FLOPS dual-core 32-bit DSP processor; 24-bit A/D and D/A converter, 48kHz sampling rate
	Input Channel	Functional component: Preamplifier 42dB, Signal Generator, Expander, 5-band Parametric Equalizer, Compressor, Automatic Gain Control (AGC), AM (Gain Sharing Automatic Mixer or Gating Automatic Mixer), Acoustic Feedback Canceler (AFC), Acoustic Echo Canceler (AEC), Adaptive Noise Suppressor (ANS), Parametric Equalizer filter type selectable (Low Shelf, High Shelf, Low Pass Filter, High Pass Filter). Physical interface: Balanced Phoenix terminals.

Output Channel	Functional component: Delay, Crossover, 31-band Graphic Equalizer, Limiter. Physical interface: Balanced Phoenix terminals.
Phantom Power	DC 48V
Input Impedance	Balanced: 20K Ω
Output Impedance	Balanced: 100 Ω
Common Mode Rejection Ratio	>60dB@50Hz
Input Dynamic Range	108dB
Frequency Response	20Hz~20KHz, \pm 0.2dB
Noise Floor	-90dBu
Signal to Noise Ratio	106dB
THD+N	\leq 0.004% @1kHz, +4dBu
Channel Isolation	104dB@1kHz
Input Range	\leq +18dBu (A-Weighting)
Crossover	Three types of high and low pass filters: Butterworth, Bessel and Linkwitz-Riley
Equalizer	Parametric Equalizer: Frequency: 20~20kHz, Gain: -15~+15dB, Bandwidth: 0.02~4 Graphic Equalizer: Frequency: 20~20kHz, Gain: -15~+15dB
Maximum Output Level	18dBu
Maximum Input Level	18dBu
Analog/Digital Dynamic Range	114dB
Digital/Analog Dynamic Range	120dB

	Equivalent Input Noise	≤-120dBu
General specification	Operating Voltage	Power adapter input: AC 100V~240V, 50Hz/60Hz; Output: DC 12V/2A.
	Maximum Power	24W
	Operating Temperature and Humidity	0°C~40°C, 10%~90%RH, No condensation
	Chassis	1U
	Product Dimensions (L×W×H)	482.4mm×210.5mm×44mm
	Net Weight	2.5kg
	Package Dimensions (L×W×H)	590mm×340mm×110mm
	Package Weight	3kg